



36 Watt Series

Desktop Type

Level VI

ATS036T - □ X X X

P : C14
A : C8

O / P Voltage

Green Mode

CEC, DoE Level VI, Energy Star, ErP Stage 2, NRCAN & GEMS Level VI

NO Load Power Consumption Less Than 0.1W

Features :

- 100-240VAC Universal Input
- Single Output to 36W
- Regulated Output With Low Ripple Noise
- Safety Agency Requirements and EMI/EMS Certified
- Private Label Marking Available
- Modified and Custom Design Available
- 1 Year Warranty

Model	O/P Voltage	O/P Current	Watt
ATS036T-□050	5.0V	5.00A	25.0W
ATS036T-□075	7.5V	4.00A	30.0W
ATS036T-□085	8.5V	3.52A	30.0W
ATS036T-□090	9.0V	3.34A	30.0W
ATS036T-□120	12.0V	3.00A	36.0W
ATS036T-□135	13.5V	2.66A	36.0W
ATS036T-□150	15.0V	2.40A	36.0W
ATS036T-□160	16.0V	2.25A	36.0W
ATS036T-□180	18.0V	2.00A	36.0W
ATS036T-□240	24.0V	1.50A	36.0W
ATS036T-□480	48.0V	0.75A	36.0W

Input

Voltage	100-240VAC
Line Frequency	50-60Hz
Current	1A Max.
Protection	Internal Primary Current Fuse , Inrush Limiting
Configuration	IEC60320/C8,C14

North America Office:
L.O.P. Enterprises Co., LTD.
 175-5489 Byrne Road,
 Burnaby, B.C. V5J 3J1 Canada
 TEL: (604)451-7999 FAX: (604)451-7958
 www.LeadingQP.com, www.LOP.ca

Output

Load Regulation	±5% (Typical)
Ripple	1 ~ 2% Vp-p Max. for Output Voltage@ Full Load
Transient Response	0.5mS for 50% Load Change Typical
Hold-up Time	10mS @ Full Load
Protection	Short Circuit Protection / Over Voltage Protection / Over Current Protection
DC Cord	22AWG / 20AWG / 18AWG / 16AWG
Ferrite Core	No (Optional)

Safety Approvals

CB / UL / cUL / FCC / GS / CE / PSE / BSMI / CCC / RCM / LPS

Electrical

Topology	Switching Flyback
Dielectric Withstand	3000VAC Primary - Secondary
Leakage Current	0.25mA
Efficiency	DoE Level VI, Energy Star, ErP Stage 2, NRCAN & GEMS Level VI Certified
EMI Conduction & Radiation	Compliance to EN55022 Class B
Harmonic Current	Compliance to EN61000-3-2,3
EMS Immunity	Compliance to IEC61000-4-2,3,4,5,6,8,11
MTBF	300,000 Calculated Hours at 25°C , by Telcordia SR-332

Environmental

Operating Temperature	0 to + 40°C
Storage Temperature	-20 to + 80°C
Relative Humidity	Operating : 20 to 80% RH Storage : 10 to 90% RH
Cooling	Natural Convection Cooling

Mechanical

Case Dimension	L101 x W51 x H34 (mm)
Weight	160g (Ref.)