



50 Watt Series

Desktop Type

Green Mode

Meet CEC Regulations & RoHS Compliance
No Load Power Consumption Less Than 0.5W

STD-□□ □□ □



Features:

- 100-240VAC Universal Input
- Single Output to 50W
- Regulated Output with Low Ripple Noise
- Meets Safety Agency Requirements and Complies EMI/EMS
- Private Label Marking Available
- Modified and Custom Designs Available
- 1 Year Warranty

Safety Approvals

CB / UL / cUL / GS / CE / PSE / BSMI / LPS

Electrical

Topology	Switching Flyback
Dielectric Withstand	3000 VAC Primary - Secondary
Leakage Current	0.25mA @ 2 Pin / 3.5mA @ 3 Pin
Efficiency	Meet CEC & Energy Star
EMI Conduction & Radiation	Compliance to EN55022 Class B
Harmonic Current	Compliance to EN61000-3-2,3
EMS Immunity	Compliance to EN61000-4-2,3,4,5,6,8,11
MTBF	50,000 Calculated Hours at 25°C, by MIL-HDBK-217F

Environmental

Operating Temperature	0 to +40°C
Storage Temperature	-20 to +80°C
Relative Humidity	Operating: 20 to 80% RH
	Storage: 10 to 90% RH
Cooling	Natural Convection Cooling

Mechanical

Case Dimensions	L115 x W53 x H38 (mm)
Weight	278g (reference)

Model	O/P Voltage	O/P Current	Watt
STD-0950P/PA	9.0V	5.0A	45.0 W
STD-1242P/PA	12.0V	4.2A	50.0 W
STD-1533P/PA	15.0V	3.3A	50.0 W
STD-1827P/PA	18.0V	2.7A	49.0 W
STD-1926P/PA	19.0V	2.6A	49.0 W
STD-2025P/PA	20.0V	2.5A	50.0 W
STD-2421P/PA	24.0V	2.1A	50.0 W
STD-4810P/PA	48.0V	1.0A	48.0 W

Input

Voltage	100-240 VAC
Line Frequency	50-60Hz
Current	1.1A Max.
Protection	Internal Primary Current Fuse, Inrush Limiting
Configuration	IEC320/ C6, C8, C14

Output

Load Regulation	± 5%
Ripple	1~2% V p-p Max. for Output Voltage @ Full Load
Transient Response	0.5ms for 50% Load Change Typical
Holdup Time	10mS @ Full Load
Protection	Short Circuit Protection/ Over Voltage Protection/ Over Current Protection
DC Cord	20AWG / 18AWG
Ferrite Core	Yes

North America Office:
L.Q.P. Enterprises Co., LTD.
175-5489 Byrne Road,
Burnaby, B.C. V5J 3J1 Canada
TEL: (604)451-7899 FAX: (604)451-7858
www.LeadingQP.com, www.LQP.ca