


6W - 12W Series Interchangeable Switching Power Supply

SWPP-XXXXYYYY-Z



Model	Input	Output
SWPP Series  Efficiency level V regulations	AC90V~264V	3V/0.2A-2.5A
		5V/0.2A-2A
		7.5V/0.2A-1.8A
		8V/0.2A-1.8A
		9V/0.2A-1.5A
		10V/0.2A-1.5A
		12V/0.2A-1.2A
		14.5V/0.2A-1A
		15V/0.2A-1A
		16V/0.2A-1A
		17V/0.2A-0.8A
		18V/0.2A-0.6A
		19V/0.2A-0.6A
		20V/0.2A-0.6A
24V/0.2A~0.5		

Safety

UL/CUL, GS, CE, CB, FCC

Input /Output Specification

ITEM	SPECIFICATION	MIN	TYP.	MAX
Input Voltage	Single Phase (Unit: VAC)	100		240
Input Voltage Range	Single Phase (Unit: VAC)	90		264
Input Frequency	Single Phase (Unit: Hz)	47	50/60	63
Input Current	Typical Input Voltage & Output at Full Road (Unit: mA)			0.5A
Ac Inrush Current	Typical Input Voltage & Output at Full Road, 25°C			30A
Efficiency	Typical Input Voltage & Output at Full Road	73%		

Output Power	12W			
Output Voltage	3V-15V			
Over Voltage Protection	120%min			
Over Current Protection	120%min			
Short Protection	Auto Recovery			
Load Regulation	±5%			

General Specification	
Operating Temp	0°C~40°C
Storage Temp	-20°~85°C
Operating Relative Humidity	5~95%RH
WithStanding Voltage	AC 3000V(Min), 5mA(Max)
Insulation Resistance	DC 500V 100MΩ(Min)

Dimension

Other types of input plug are also available

North America Office:
L.Q.P. Enterprises Co., LTD.
 175-5489 Byrne Road,
 Burnaby, B.C. V5J 3J1 Canada
 TEL: (604)451-7899 FAX: (604)451-7858
www.LeadingQP.com, www.LQP.ca