


6W Series Wall Mount Switching Power Supply

SWPP-XXXXYYYY-Z



Input Connector

US, Euro, UK, Aus input plug

Model	Input	Output
<p>SWPP Series</p>  <p>Efficiency level V regulations</p>	AC90V~264V	3V/0.2A-1.5A
		5V/0.2A-1.2A
		7.5V/0.2A-0.8A
		8V/0.2A-0.6A
		9V/0.2A-0.66A
		10V/0.2A-0.6A
		12V/0.2A-0.5A
		14.5V/0.2A-0.4A
		15V/0.2A-0.5A
		16V/0.2A-0.35A
		17V/0.2A-0.3A
		18V/0.2A-0.3A
		19V/0.2A-0.3A
		20V/0.2A-0.3A
24V/0.2A~0.25		

Safety

UL/CUL, GS, CE, CB, FCC

Input /Output Specification

ITEM	SPECIFICATION	MIN	TYP.	MAX
Input Voltage	Single Phase (Unit: VAC)	100		240
Input Voltage Range	Single Phase (Unit: VAC)	90		264
Input Frequency	Single Phase (Unit: Hz)	47	50/60	63

Input Current	Typical Input Voltage & Output at Full			350mA
Ac Inrush Current	Typical Input Voltage & Output at Full			30A
Efficiency	Typical Input Voltage & Output at Full	73%		
Output Power	5W			
Output Voltage	5V~24V			
Over Voltage Protection	120%min			
Over Current Protection	120%min			
Short Protection	Auto Recovery			
Load Regulation	±5%			

General Specification				
Operating Temp	0°C~40°C			
Storage Temp	-20°~85°C			
Operating Relative Humid	5~95%RH			
WithStanding Voltage	AC 3000V(Min), 5mA(Max)			
Insulation Resistance	DC 500V 100MΩ(Min)			

General Specification

Other types of input plug are also available

North America Office:
L.Q.P. Enterprises Co., Ltd.
 175 - 5489 Byrne Road, Burnaby,
 BC, Canada, V5J 3J1

TEL: (604)451-7899 FAX: (604)451-7858
www.leadingQP.com, www.LQP.ca