



3RD ANGLE PROJECTION		SIGNATURE	DATE	L.Q.P Ent. CO., Ltd			
Q' TY	TOLERANCES	DRAWN BY: 农金莲	05-17-07		P/N: CAB300-3		
	DIM: ±5	CHECK BY:			SCALE: 1:1.5	UNIT: MM	REV.: A/0
	ANGLE: 5°	BDD APPD.			SHEET 1 OF 2		

8 7 6 5 ↓ 4 3 2 1

H 客户: DPL

WIRE LIST

J1	COLOR	J2	*L	CUT WIREL	*L
1	BLACK	TERMINAL +BLACK	2650±50	650±5 2000±15	#20 #20
2	BROWN		600±20	650±5	#22
5	PINK+3A FUSE	TERMINAL	600±20	430±5	#22
6	ORANGE+TERMINAL+ORANGE	CUT	2050±50	650±5 1400±15	#20 #14
9	3A FUSE+RED	CUT	2600±50	2410±15	#20
10	YELLOW	H.S.TUBE	200±10	200±3	#22
11	WHITE	CUT	2000±50	2000±15	#22
12	GRAY	CUT	600±20	600±5	#22
13	GREEN	CUT	600±20	600±5	#22
14	PURPLE	CUT	600±20	600±5	#22
15	BLUE	CUT	600±20	600±5	#22

Short

15	H. S. TUBE	∅6.0 UL BLACK L=22mm	2PC	
14	H. S. TUBE	∅8.0 UL BLACK L=40mm	1PC	
13	HOOD	250 FEMALE HOOD CLEAR	2PC	
12	TERMINAL	JINHUI:J704-BS-2	4PC	
11	H. S. TUBE	∅2.0 UL BLACK L=20mm	3PC	
10	FUSE HOLDER	HUA HENG:FH-619 Black,Two Side With wire	2SET	
9	FUSE	3A FUSE 32V	2PC	
8	SCREW MOLD	T-3120 PVC EY-11#(BLACK)15P		
7	SCREW	#4-40 UNC 4*47mm NICKEL PLATED	2PC	
6	OUTER MOLD	T-1234 PVC BY-11# (BLACK) 45P		
5	INNER MOLD	T-2235 PE EY-12#		
4	DB 15M	INSU:BLACK SHELL NICKEL PLATED	1PC	
3	CABLE	UL1568 22AWG Wire Tinned copper PVC Color: Brown;Pink;Yellow;White;Gray;Green	Look	
		Purple;Blue Rated voltage:300V,Temperature:105℃	WIRE LIST	
2	CABLE	UL1568 14AWG Wire Tinned copper PVC Color: orange	Look	
		Rated voltage:300V, Temperature:105℃	WIRE LIST	
1	CABLE	UL1568 20AWG Wire Tinned copper PVC Color:Black	Look	
		orange;red; Rated voltage:300V, Temperature:105℃	WIRE LIST	
NO		DESCRIPTION	Q'TY	REMARK

NOTE:
1. UNIT:mm
2. TEST:

J3	COLOR	J4	*L	CUTL	AWG
CUT	ORANGE	TERMINAL	1400±50	1400±15	#14

a. EACH CONDUCTOR MUST PASS CONTINUITY TEST AND SHORT, OPEN, INTERMITTENT, MISWIRING SITUATION OCCUR IS NOT PERMITTED,
b. THE INSULATION RESISTANCE BETWEEN EACH CONDUCTORS IS 2M OHM MIN
3. EVERY BAG HAS THIS SINGLE ORANGE WIRE AND THE CAB 300-3
4. WITH RoHS COMPLIANT.

3RD ANGLE PROJECTION		SIGNATURE	DATE	L.Q.P Ent. Co., Ltd			
Q' TY	TOLERANCES	DRAWN BY: 农金莲	05-17-07		P/N: CAB300-3		
	DIM: ±5	CHECK BY:			SCALE: 1:1.5	UNIT: MM	REV.: A/0
	ANGLE: 5°	BDD APPD:			SHEET 2 OF 2		

8 7 6 5 ↑ 4 3 2 1