



NOTENS:

1.CONNECTION:



2.TESTING PARAMETER:

INSULATION RESISTANCE:DC300V 10MΩ MIN
 CONDUCTOR RESISTANCE 1Ω MAX

E	PVC/MOLD	4001 45P BLACK PVC;MOLD; 213-137	
D	JACK	DC JACK 5.5*2.1 NICKEL PLATED	
C	PVC/MOLD	4001 45P BLACK LOW TOXIC RoHS PVC MOLD:213-279	
B	PLUG	DC PLUG ø5.5*2.1*11 TUNING FORK WITH GROOVE NICKEL PLATED	
A	CABLE	UL2468 OD2.1*4.2mm 18AWG 41/0.16BC*2F BLACK Flat Cable	
ITEM	DES	SPECIFICATION	REMARKS

TOLERANCE		L.Q.P. Enterprises Co., Ltd.	CUSTOMER NO	445	PART NO	PART NAME		
.X	±0.2		DRAW NO	04450080	APPROVED	Right-angle DC PLUG 5.5*2.1 TO DC JACK 5.5*2.1		
.XX	±0.1		UNITS	SCALL	FREE	CHECKED	MODIFY DATE	
.XXX			mm			DRAWN	Gu xiaolin	DATE

REV	MODIFY DESCRIPTION	DATE
sample		