



NOTENS:  
1.CONNECTION:



2.TESTING PARAMETER:  
INSULATION RESISTANCE:DC500V 20MΩ MIN  
CONDUCTOR RESISTANCE 1Ω MAX

E	PVC/MOLD	4001# 45P BLACK PVC;MOLD; 213-137	
D	JACK	DC JACK 5.5*2.1 NICKEL PLATED	
C	PVC/MOLD	4001# 45P BLACK PVC MOLD;213-279	
B	PLUG	DC PLUG φ5.5*2.1,TUNING FORK WITH GROOVE NICKEL PLATED.BLACK INSULATION	
A	CABLE	UL2468 OD1.8*3.6mm 22AWG(17/0.16BC)*2F BLACK Flat Cable	
ITEM	DES	SPECIFICATION	REMARKS

TOLERANCE			CUSTOMER NO	445	PART NO		PART NAME		
.X	±0.2		DRAW NO	04450087	APPROVED		Right-angle DC PLUG 5.5*2.1 TO DC JACK 5.5*2.1		
.XX	±0.1		UNITS	SCALE	FREE	CHECKED		MODIFY DATE	
.XXX			mm			DRAWN	HL	DATE	12-31-2011
L. Q. P. ENTERPRISES CO., LTD									

REV	MODIFY DESCRIPTION	DATE
sample		